

# Технический паспорт продукта Характеристики

## LC3D120AP7

on rail star delta starter TeSys LC3-D - coil 230 V AC



### Main

Range of product	TeSys
Device short name	LC3D
Product or component type	Contactors
Poles description	3P
Utilisation category	AC-3
Motor power kW	5.5 kW at 220/230 V AC 50/60 Hz 11 kW at 380/400 V AC 50/60 Hz 11 kW at 415 V AC 50/60 Hz 11 kW at 440 V AC 50/60 Hz
Auxiliary contacts available on each contactor	1 NC for KM1 star contactor
Interlocking type	With start delta mechanical interlock
Operating rate	30 cyc/h
Control circuit voltage	230 V AC 50/60 Hz
Mounting support	35 mm symmetrical DIN rail

### Complementary

Starting time	30 s
Width	175 mm
Height	124 mm
Depth	139 mm
Product weight	1.53 kg

### Environment

RoHS EUR conformity date	0844
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.