

RAY MINI

1T4203

LIGHT SOURCE **LED MONOCHROMATIC** COLOUR TEMPERATURE **3000K** NUMBER OF LAMPS **1** POWER (SOURCE) **30W**
 CRI **RA84** BEAM ANGLE **MWFL** COLOUR **PLASTER WHITE** POWER SUPPLY TYPE **ELECTRONIC**
 FEEDING VOLTAGE (V-AC) **220-240V-AC** INSULATION CLASS **CLASS 1** GLOBAL IP OR HOUSING **IP20** F CLASS **YES**
 CERTIFICATIONS **ENEC** LIGHT EFFECTS **FLOOD LIGHTING**



CONCEPT

Professional adjustable LED projector.

MATERIALS

Die-cast aluminium body painted with deep black or plaster-white finish. Front ring made of black polycarbonate, high temperature plastic polymer. Adjustable from 0° to -90° in the vertical plane and 359° in the horizontal plane. Mechanical aiming lock in the vertical plane and blocking equipped with a friction system in the horizontal plane. The centre of gravity always remains in axis with the track irrespective of where it is aimed.

OPTIC


High efficiency LED Chip on Board Ra 84/Ra 97. Metallised polycarbonate precision optic with ellipsoidal convex facets.

INSTALLATION

Electrified track mounting.

POWER SUPPLY


Electronic and DALI driver built into luminaire body. 220-240V-AC 50/60Hz



All the measures are expressed in mm


Photometries

3000K Ra84	H(m)	D(m)	Emax(lx)			
				Fixture Power	Source Flux	Fixture Flux
33W	1	0.84	6191			
4072lm	2	1.67	1548			
3539lm	3	2.51	688			
107lm/W	4	3.35	387			
6222cd	5	4.18	248			



Accessory Codes


Optical



1T1708

Filter

Parallel ribbed glass light blade filter. This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T1709

Filter

Wired refractive flat glass diffusive filter. This softens the luminous effect. To be completed with additional holder ring for Cloud, Ray Mini, Magma and Store. Diameter 70 mm.



1T1712

Filter

Interference flat glass chromatic filter. Red. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T1713

Filter

Interference flat glass chromatic filter. Green. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T1714

Filter

Interference flat glass chromatic filter. Blue. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T1715

Filter

Interference flat glass chromatic filter. Yellow. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T1716

Filter

Interference flat glass chromatic filter. Magenta. To be completed with additional holder ring for Cloud, Ray Mini, Magma, Store and Keplero Mini HE. Diameter 70 mm.



1T6507

Filter

Art filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Vivid +. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6511

Filter

Food filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Vegetable. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6509

Filter

Food filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Fish. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6506

Filter

Art filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Halogen +. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6510

Filter

Food filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Bread. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6512

Filter

Beauty filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Beauty. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T6508

Filter

Food filter. Interference glass filter to vary the colour temperature of light. Diameter 70 mm. Meat. To be completed with additional holder ring for Cloud, Ray Mini, Store.



1T1711

Grid

Anti-glare grid. Black lacquered metal honeycomb structure. To be completed with additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE. Diameter 70 mm. Max HIT-Tc-CE 35W.



1T3143

Ray Shade


Asymmetric screen in anodized diffusive aluminum, black painted outside. Complete with blade light filter. Ideal for a wall washer effect. To be combined with spot and flood optics. Diameter 80 mm.



1T3432

Zoom

Zoom. Optical system consists of flat convex lens in optical glass, specular reflector in anodized aluminium and diffusive holographic filter. To be used after removing the existing optic. It allows to obtain a variable beam from 15° to 60°. It can not be used with NSP and hybrid optics. Diameter 80 mm.



1T3142

Cut-Off

Cut-off Tube. Allows for the beam to be focused while removing the fall-off component. Diameter 80 mm.




1T6522

Screen

Protective screen. Diameter 80 mm.


Electrical



1T2220

Adapter

Ceiling mounting adapter for electrified track type projectors. Black. Electronic. Dimension Ø100 H32.



1T2221

Adapter

Ceiling mounting adapter for electrified track type projectors. White. Electronic. Dimension Ø100 H32.



1T2222

Adapter


Recessed mounting adapter for electrified track type projectors. Black. Electronic. Dimension Ø130 H60. Recess hole diameter 105/125 mm. To be completed with 1T2220.



1T2223

Adapter

Recessed mounting adapter for electrified track type projectors. White. Electronic. Dimension Ø130 H60. Recess hole diameter 105/125 mm. To be completed with 1T2221.



1T2219

Adapter

Ceiling mounting adapter for electrified track type projectors. Aluminium. Electronic. Dimension Ø100 H32.



1T2224

Adapter

Recessed mounting adapter for electrified track type projectors. Aluminium. Electronic. Dimension Ø130 H60. Recess hole diameter 105/125 mm. To be completed with 1T2219.

Installation



1T3727

Holder Ring

Black painted aluminium holder ring for the accessories.